

		Data type							
		OSD		CTD		PFL		APB	
		Percent rejected levels							
No.	Quality check	<i>T</i>	<i>S</i>	<i>T</i>	<i>S</i>	<i>T</i>	<i>S</i>	<i>T</i>	<i>S</i>
1	Crude parameter range check	0.078	1.740	0.059	0.886	0.030	0.320	3.118	0.640
2	Spike check	0.010	0.003	0.001	0.001	0.005	0.008	0.004	0.003
3	Constant value check	0.004	0.114	0.007	0.114	0.004	0.128	0.024	0.043
4	Multiple extrema check	0.092	0.009	0.056	0.043	0.062	0.074	0.129	0.046
5	Vertical gradient range check	0.050	0.213	0.069	0.147	0.023	0.044	0.042	0.093
6	Local climatological range check	2.669	5.533	2.375	3.180	1.079	1.746	7.088	9.170
7	Sample depth vs. local digital bathymetry check	2.877	2.877	3.588	3.588	0.165	0.163	9.268	9.268
8	Percentage levels flagged	5.517	0.793	2.048	2.645	0.197	0.680	8.421	7.204
	Percentage rejected levels	5.52	9.55	5.88	7.61	1.30	2.06	16.98	17.78
	Percentage profiles with at least one rejected level	20.52	29.99	23.98	27.78	14.09	15.93	35.69	50.13